

newhey

COLORTEC+ | PLATINUM

July 2017

Product Specifications

Quality Name	Platinum		
Construction	Colortec+		
Description	Cut Pile Patterned Tufted Carpet		
Fibre Content	80% Wool / 20% Nylon		
Country of Origin	U.K.		
	Metric	Imperial	Tolerance
Yarn Count	R740/3	3/42's	
Machine Gauge	25.2/dm	6.4 per inch	
Stitches per inch	39.4/dm	10 per inch	±3%
Tuft density	992.9/dm	64.0 per sq inch	±3%
Pile Height above Back	7.5mm	0.30"	±10%
Total Carpet Thickness	10.0mm	0.41"	±10%
Total Pile Weight	1800g/m ²	53.10oz/yd ²	±10%
Total Carpet Weight	2470g/m ²	72.87oz/yd ²	±10%
Product Width	4.00m		±1.25%
Backing Materials	Woven Polyester, EVA (ethylene vinyl acetate), evobac; 100% recycled PET-Post consumer plastic		

Performance Testing/Suitability

Performance BS EN 1307	Class 33; Heavy Commercial Use
Luxury Class	LC4

E.U Standards

BS EN 13501-1	Cfl-s1
----------------------	--------

U.S Standards

ASTM E648 Critical Radiant Flux	Class 1
AATCC 134 Electrostatic Propensity	less than 3.5 kV
ASTM D2859 Surface Flammability	Passes
ASTM E662 Smoke Density	Less than 450

Colour Fastness

Light	Minimum 5
Shampooing	Minimum 4
Water	Minimum 4
Rubbing	Minimum 4

Installation Methods

Carpet should be installed in accordance with Newhey installation specifications. This may vary subject to type of installation and site conditions. For guidance and advice please contact a Newhey representative.

Maintenance

Proper maintenance and care is critical to the long term performance of any carpet and should be written in to the specification of a project. For guidance and advice please contact a Newhey representative.

Newhey Carpets reserve the right to change specification and construction materials due to raw material shortages or for the purposes of product improvements. All specifications are subject to normal manufacturing tolerances. Dye lots may vary from batch to batch.

